

SANIFAST SYSTEM



SANIFAST SYSTEM BASE

DESCRIPTION:

Double peristaltic pump dosing system for continuous mixing and dosages of chlorine dioxide WL-SANIFAST.

Microprocessor-controlled vertical dosing pump with frequency adjustment display. With the possibility of receiving a digital pulse signal, with divider and multiplier for 999, the possibility of receiving a signal from 0 or 4 to 20 mA, or from 0 to 10 volts, with "Batch" function, the possibility of setting display the amount of product for each injection, with level sensor and the possibility to re-launch the alarm signal. Complete with bottom valves and 3/8 "x6" injections with VITON seals, double ceramic ball valves, Teflon diaphragm. PVDF head 2 l / h against 15 bar.



SANIFAST SYSTEM PLUS

DESCRIPTION:

Triple dosing pump panel for continuous mixing and dosages of chlorine dioxide components and of anticorrosive filming additive (FILMAX series).

Microprocessor-controlled vertical dosing pump with frequency adjustment display. With the possibility of receiving a digital pulse signal, with divider and multiplier for 999, the possibility of receiving a signal from 0 or 4 to 20 mA, or from 0 to 10 volts, with "Batch" function, the possibility of setting display the amount of product for each injection, with level sensor and the possibility to re-launch the alarm signal. Complete with bottom valves and 3/8 "x6" injections with VITON seals, double ceramic ball valves, Teflon diaphragm. PVDF head 2 l / h against 15 bar.

FORMATS:

SANIFAST SYSTEM BASE with two pumps, article code WLSANIDOSBA.

SANIFAST SYSTEM BASE with three pumps, article code WLSANIDOSPL.