

ECOGRYP



DESCRIPTION:

Green putty paste. It is a ready-to-use product for the assembly of hydraulic, hygienic, sanitary and industrial equipment and fittings. Anti-seize, anti-oxidant, excellent preservative for frayed hemp and canvas-rubber gaskets, mineral fibers, etc.

COMPOSITION:

Petroleum greases, stearates and ore charges.

APPLICATIONS: It guarantees a perfect tight on fittings and threaded or flanged couplings etc. It is used together with hemp on threaded couplings, while on flanged couplings it has to be spread on gaskets of asbestos, fiber, rubber, etc.

USES:

Suitable for hot and cold water supply pipes, as well as air piping and methane, gas or food liquids mains.

TECHNICAL DATA:

Appearance	creamy paste
Color	green or gray
Relative density	$1,65 \pm 0,010 \text{ g/cm}^3$
Working temperature	$-35 \div +130 \text{ }^\circ\text{C}$
Maximum working overpressure for gas	1 Bar
Maximum working temperature for gas	$80 \text{ }^\circ\text{C}$
Flash point	$>300 \text{ }^\circ\text{C}$
Viscosity at $100 \text{ }^\circ\text{C}$	$65/1 \text{ s mm}^2/\text{s}$
Water solubility	insoluble
Working data for H_2O	up to $115 \text{ }^\circ\text{C}/2 \text{ Bars}$

PRODUCT:

It does not contain solvents; non-toxic when inhaled or touched.

PACKAGING:

Cans of 0,400 Kg, 1 Kg, 30 Kg.

Last update: 03.04.2023



PRODOTTI CHIMICI E TECNICI - CHEMICAL AND TECHNICAL PRODUCTS

FACOT CHEMICALS Srl - Via Crema 44, 26010 Capralba CR, Italy - Tel. +39 0373450642 - info@facot.it - www.facotchemicals.com



CHEMISTRY IN ACTION