

ECOLYNER 360°



Mark tracks for walls and floors

DESCRIPTION:

Fast-drying spray paint for making on walls and floors, available in various colors. Required when reporting on the construction site of various plants to be built such as: gas, electric systems, hot and cold water. Can be used outdoors on industrial floors **even overhead**.

APPLICATION:

Its quick drying, tenacious adhesion to substrates, resistance to abrasion and friction to make it suitable to trace, mark or define spaces, areas, corridors, construction sites, factories, roads, parking lots, sports fields, wood or pallets.

HOW TO USE:

Clean the surface from fat, water or parts that are detached, shake a few minutes spray with past read and constants to avoid leaking drops, while maintaining the cylinder at a distance of 25 – 30 cm **even overhead**. Removing paint with acetone and/or nitro.

Available colors red, black, yellow, blue.

TECHNICAL DATA:

Appearance	liquid, various colors
Odor	characteristic of solvent
Volume of containers	520 ml
Volume of product	400 ml
Pressure at 20 °C	4,0 ± 0,3 Bar
Pressure test of the cylinder	18 Bar
Explosion limits	1,8 ± 9,5 % in volume
Relative density of the liquid phase	0,900 ± 0,005 g/ml
Relative density of the mixture	0,775 ± 0,025 g/ml
Water solubility	insoluble

PACKAGING:

Spray 400 ml, boxes of 12 pieces.

Last update: 03.04.2023



PRODOTTI CHIMICI E TECNICI - CHEMICAL AND TECHNICAL PRODUCTS

FACOT CHEMICALS Srl - Via Crema 44, 26010 Capralba CR, Italy - Tel. +39 0373450642 - info@facot.it - www.facotchemicals.com



CHEMISTRY IN ACTION