

# ELASTUK STRIP



## DESCRIPTION:

Performed putty stripes.

Suitable for applications on cookers, drains, Jacuzzis, embedded sinks. Available in rolls of the following sizes:

- 15 mm x 2 mm x 22,5 m (boxes of 18 pieces)

Adheres to many types of media such as metal/ABS, metal/PVC, metal/polystyrene high impact. ELASTUK STRIP is also used to seal the windows with metal frames and for junctions of sheets or panels screwed.

## ISTRUZIONI FOR USE:

Surface preparation: surfaces must be clean and dry, without grease or oil.

Dimensions of the joint: no limitations, the section must be a little bit bigger to that of the joint.

Apply the performed stripe on the support exerting a light pressure. Then remove the protection paper and join the parts. A light pressure on it must always be exerted.

Application temperature: over + 5 °C.

## TECHNICAL DATA:

|   |                               |
|---|-------------------------------|
| Base  | butyl - polyisobutylene       |
| Appearance  | gummy solid                   |
| Color   | anthracite gray               |
| Specific weight (rif. ASTM D 792-91)                      | 1,60 ÷ 1,70 g/cm <sup>3</sup> |
| Penetration at cone (150 g) at 20 °C (rif. ASTM D 217-94) | 40 ÷ 50 dmm                   |
| Resistance to loss of cohesion                            | 110 ÷ 115 °C                  |
| Application temperature                                   | +5 ÷ +40 °C                   |
| Working temperature                                       | -30 ÷ +70 °C                  |
| Water absorption  | negligible                    |

## STORAGE:

ELASTUK STRIP stored in its original packaging, in dry and well ventilated place at temperatures between 5 °C to 30 °C has a duration of 12 months from date of manufacture.

Last update: 03.04.2023

