


EPOSTIX



Fast setting epoxy grout

DESCRIPTION:

Single-piece bicomponent epoxidic dope, for a rapid repair of leaks.

INSTRUCTIONS FOR USE AND APPLICATION:

Instructions:

- Clean the area to be repaired, removing rust and scales.
- Do not apply on pipes under pressure
- Cut a sufficient piece of EPOSTIX
- Two minutes are needed for the repair
- Amalgamate the piece
- Press the product on the section to be repaired
- Remove the excess of product, and smooth with your hands
- Ready after 20 minutes
- Maximum setting time: 1 hour

Applications:

- Hand formable, adaptable, ready-to-use and user-friendly.
- It stops leaks, and rapidly plug holes and cracks
- Hardens in 20 minutes
- Works inside water
- Wide range of temperatures
- Odorless, non-toxic, without solvents; it does not cracks; it adheres
- Can be turned, pierced, threaded, worked, varnished after its hardening

Uses:

It can be used to repair underwater pipes, swimming pools, tanks, couplings, permanent seals, in houses, cars, boats and caravans. It repairs metals, plastic, wood, etc.

WARNINGS:

- Do not touch your eyes with dirty hands (dirty with EPOSTIX) . In case wash them with plenty of water and consult a doctor.
- Wash your hands using water and soap until they are completely clean. Sensible skins can get irritated by resin and ammonia traces contained in this product. Use gloves when skin is delicate.
- Keep out of children's reach
- Do not ingest the product
- It can be dangerous

GUARANTEE: FACOT CHEMICALS declines all responsibility for any misuse of this product in risky areas, dangerous places with pipes under pressure. The only guarantee is the substitution of damaged EPOSTIX.

Last update: 03.04.2023



PRODOTTI CHIMICI E TECNICI - CHEMICAL AND TECHNICAL PRODUCTS

FACOT CHEMICALS Srl - Via Crema 44, 26010 Capralba CR, Italy - Tel. +39 0373450642 - info@facot.it - www.facotchemicals.com



CHEMISTRY IN ACTION