


FILMAX-San



Regenerating sanitary plants

DESCRIPTION:

Corrosion protection, regenerating for sanitary obsolescent plants which have undergone corrosion processes advanced over the years (rust, limestone, silica litter).

The product serves as a protective coating of the pipes after the descaling against rust and scale with the use of the product ZINCONEX-AI (acid descaling with corrosion inhibitors).

It is not harmful to human health and the environment and is classified FDA for food use.

DOSAGE:

Recommend to dose FILMAX-San a rate of 1,5 ÷ 2 % in the water plant.

HOW TO USE:

Occurred after the pickling of rust and descaling of limestone or silica to circulate for at least 12 ÷ 24 hours in the sanitary creating a recirculation of the system and after emptying necessary to wash with water. The product can remain in the plant even longer and would not cause any damage.

TECHNICAL DATA:

Appearance	liquid
Odor	straw
Color	weak
pH	11,0 ÷ 12,0
Boiling point	>100 °C
Relative density	1,012 kg/lt
Water solubility	complete

PACKAGING:

Bottle 1 liter.

Tank 5 liters.

Last update: 04.04.2023



PRODOTTI CHIMICI E TECNICI - CHEMICAL AND TECHNICAL PRODUCTS

FACOT CHEMICALS Srl - Via Crema 44, 26010 Capralba CR, Italy - Tel. +39 0373450642 - info@facot.it - www.facotchemicals.com



CHEMISTRY IN ACTION