

KOLGAS



DESCRIPTION AND CHARACTERISTICS:

Light brown plastic dope for the tight of nipples and unthreaded fittings. It always keeps soft, elastic and unchanged during the time preventing oxydation and corrosion of threads. Use together with hemp or cloth, mineral fibres gaskets or rubber rings etc. It has an anti-drying action on gaskets or rings, and an antiscuff action on threads.

COMPOSITION:

Mixture of petroleum greases with a high melting point and inert charges.

APPLICATIONS:

To be specifically used for gas tight, methane tight, steam tight, water tight, food liquids tight etc.

Product conforming to the UNI-EN 751/2 classes A, Arp.

TECHNICAL DATA:

Specific weight

Working temperature for hot water

Working temperature for gas and steam

Product

about $1,385 \pm 10 \% \text{ g/cm}^3$

from -35 to $+130 \text{ }^\circ\text{C}$ / 7 Bars

from -35 to $+70 \text{ }^\circ\text{C}$ / 5 Bar

Non-toxic when inhaled or touched

Without solvents

PACKAGES AVAILABLE:

460 g can, boxes of 48 pieces.

Last update: 17.04.2023



PRODOTTI CHIMICI E TECNICI - CHEMICAL AND TECHNICAL PRODUCTS

FACOT CHEMICALS Srl - Via Crema 44, 26010 Capralba CR, Italy - Tel. +39 0373450642 - info@facot.it - www.facotchemicals.com



CHEMISTRY IN ACTION