

# KOLGAS-UNI

In conformity to UNI EN 751/2 Cl. A-Arp



## DESCRIPTION AND CHARACTERISTICS:

Dark green putty paste KOLGAS-UNI is a plastic sealant for threaded and unthreaded joints tight. KOLGAS-UNI always keeps soft, elastic and unchanged during the time preventing oxydation and corrosion of threads. Use together with hemp or cloth, mineral fibres gaskets or rubber rings etc. It has an anti-drying action on gaskets or rings, and an antiscuff action on threads.

## COMPOSITION:

Mixture of petroleum greases with a high melting point and inert charges.

## APPLICATIONS:

To be specifically used for gas tight, methane tight, steam tight, water tight, food liquids tight, etc. It is not suitable for use with LPG and OXYGEN.

## TECHNICAL DATA:

Appearance	dark green paste
Odor	characteristic
Specific weight	1,274 ± 0,010 g/cm <sup>3</sup>
Working temperature for hot water and steam	from -35 to +130 °C / 7 bars
Working temperature for gas	from -35 to +70 °C / 5 bars
Flash point	> 300 °C
Water solubility	none
Product	Non-toxic when inhaled or touched Without solvents

## PACKAGES AVAILABLE:

400 g can, boxes of 48 pieces.

Last update: 17.04.2023



PRODOTTI CHIMICI E TECNICI - CHEMICAL AND TECHNICAL PRODUCTS

FACOT CHEMICALS Srl - Via Crema 44, 26010 Capralba CR, Italy - Tel. +39 0373450642 - [info@facot.it](mailto:info@facot.it) - [www.facotchemicals.com](http://www.facotchemicals.com)



CHEMISTRY IN ACTION