


PLASTOPAK



DESCRIPTION:

Insulating material with self-wrapping rigid PVC foil with smooth gray surface suitable for the finishing of thermal insulation.

The sheet adheres perfectly to all pre-insulated cylindrical surfaces. Lightness and manageability are practical prerogatives of this self-extinguishing product that does not drip and protects the insulation, improving its appearance.

TECHNICAL DATA:

Nature components or trade name	100 % PVC rigid, additives, grey color 7059
System of production	Calendaring
Format	bobine da H 100 cm x 25 ml (25 m ²)
Weight	414 g/m ²
Thickness foil	between 0,30 and 0,35 mm
Operating temperature	from -25 °C to +70 °C
Reaction to fire	omol. MI7000C50CD100009
Lambda thermal conductivity	0,16 W (m-K)
Self-extinguishing CL1	

Material is: Anisotropic and two-sided equal.

USE:

Insulating material in view with insulating component directly exposed to flames for covering ventilation and heating pipes.

INSTALLATION:

It is placed on an insulating or fireproof support and fixed with special plastic rivets and at the ends with self-extinguishing PVC or aluminum tape.

Last update: 18.04.2023



PRODOTTI CHIMICI E TECNICI - CHEMICAL AND TECHNICAL PRODUCTS

FACOT CHEMICALS Srl - Via Crema 44, 26010 Capralba CR, Italy - Tel. +39 0373450642 - info@facot.it - www.facotchemicals.com



CHEMISTRY IN ACTION