

# SILIT



## DESCRIPTION:

Water repellent composed grease added with silicones.

## CHARACTERISTICS:

Oxidation resistant and corrosion proofing; hot and cold waterproof. It does not emulsify with water and resists to medium temperatures.

## APPLICATIONS:

For the greasing of bearings working inside furnaces, driers, stoves and ventilators. For a permanent lubrication of valves, taps, pumps, compressors, meters, stuffing boxes, etc.

## INSTRUCTIONS FOR USE:

Apply by means of a spatula or of a special lubricator. Good pumpability.

## TECHNICAL DATA:

|                                  |                       |
|----------------------------------|-----------------------|
| Appearance                       | smooth-textured straw |
| Odour                            | characteristic        |
| Water solubility                 | insoluble             |
| Density                          | 0,95 ± 0,01 g/ml      |
| Penetration (ASTM D 217 @ 25 °C) | 265 ÷ 295 mm/10       |
| Dropping point (ASTM D 566)      | 150 ÷ 170 °C          |

Last update: 19.04.2023



PRODOTTI CHIMICI E TECNICI - CHEMICAL AND TECHNICAL PRODUCTS

FACOT CHEMICALS Srl - Via Crema 44, 26010 Capralba CR, Italy - Tel. +39 0373450642 - [info@facot.it](mailto:info@facot.it) - [www.facotchemicals.com](http://www.facotchemicals.com)



CHEMISTRY IN ACTION