

SILIT SPRAY



DESCRIPTION:

Spray silicone oil, anti-adhesive, lubricating, protective, antioxidant, water-repellent.

CHARACTERISTICS:

It is a multiuse silicone oil useful also as an anti-adhesive for soldering. It prevents soldering scales from adhering on surfaces, thus avoiding scraping operations. When sprayed on welder nozzles it guarantees uniform solderings without blowholes. It lubricates and protects from corrosion all mechanical parts in humid places. It extends cutting tools life, and makes gaskets, plastic and rubber parts elastic and lasting. It eliminates humidity and dust from electric systems. When used inside the battery ignition calotte and on battery terminals it repels humidity and prevents from corrosion.

WARNINGS:

Can under pressure. Protect from sun-rays and do not expose to a temperature higher than 50 °C. Do not pierce or burn the can even after using it. Do not spray on flames or on incandescent bodies. Avoid direct inhalation. In case of eye contact, wash them with water. Keep the can out of children's reach.

TECHNICAL DATA:

Viscosity (sec.) cup 2A	110 sec.
Working temperature	from -33 to +178 °C
Specific weight	0,66 g/cm ³
Can volume	520 ml
Aerosol product volume	400 ml
Pressure	4 Bars
Aerosol product flash point	Lower than 21 °C
Propellent flash point	Lower than 0 °C
pH	Unmeasurable
Water solubility	Insoluble
Foaming power	Not foaming

Last update: 19.04.2023



PRODOTTI CHIMICI E TECNICI - CHEMICAL AND TECHNICAL PRODUCTS

FACOT CHEMICALS Srl - Via Crema 44, 26010 Capralba CR, Italy - Tel. +39 0373450642 - info@facot.it - www.facotchemicals.com



CHEMISTRY IN ACTION