

WL-CART-FA HOT

Water-line, cartridge with wound polypropylene thread



DESCRIPTION:

Wound polypropylene thread filtering from 10 to 50 micron (throw-away cartridge). Cartridge for filtration of: sand, scale, lime, rust, fine particles.

Domestic use: filtration of drinking water, protection of taps, boilers, washing machines and other installations not for potable water.


Technical use: pre-filtration for water-pumps, irrigation systems, protection of industrial installations; filtration of water and other liquids in industrial applications: chemical, petrochemical, photographic, electroplating, pharmaceutical. **Average life-span:** 3 - 6 months. **Maintenance:** none.

TECHNICAL USE:

Maximum temperature of use 80 °C. Non-toxic materials. **Standard filtering septum:** polypropylene yarn. **Standard internal core:** reinforced polypropylene. Polyphosphate container in crystals for food use (disposable cartridge). Anti-scale and anti-corrosion protection for domestic and industrial installations.

Type of cartridge with wound polypropylene thread

Suitable container	Optimal flow l/h	mm A	mm B	mm C
5"	500	125	61	28
7"	700	173	61	28
10"	1000	250	61	28
20"	2000	505	61	28



Filtration degrees available, in micron:

10 – 25 – 50 micron

Last update: 20.04.2023



PRODOTTI CHIMICI E TECNICI - CHEMICAL AND TECHNICAL PRODUCTS

FACOT CHEMICALS Srl - Via Crema 44, 26010 Capralba CR, Italy - Tel. +39 0373450642 - info@facot.it - www.facotchemicals.com



CHEMISTRY IN ACTION