

DOSING SYSTEM



DOSING SYSTEM BASE

DESCRIPTION:

Dosing system with double peristaltic pump for continuous mixing and dosing of Chlorine Dioxide produced by WL-SANIFAST.

Vertically mounted microprocessor metering pump with frequency adjustment display. With the possibility of receiving a digital pulse signal, with divider and multiplier for 999, the possibility of receiving a signal from 0 or 4 to 20 mA, or from 0 to 10 Volts, with "Batch" function, the possibility of setting the quantity of product for each injection on the display, with level sensor and the possibility of relaunching the alarm signal. Complete with foot valves and 3/8 4x6 injections with Viton gaskets, double ceramic ball valves, Teflon diaphragm. PVDF head 2 l/h against 15 bar.



DOSING SYSTEM PLUS

DESCRIPTION:

Panel with triple dosing pump for continuous mixing and dosing of Chlorine Dioxide and anti-corrosive filming (FILMAX series).

Vertically mounted microprocessor metering pump with frequency adjustment display. With the possibility of receiving a digital pulse signal, with divider and multiplier for 999, the possibility of receiving a signal from 0 or 4 to 20 mA, or from 0 to 10 Volts, with "Batch" function, the possibility of setting the quantity of product for each injection on the display, with level sensor and the possibility of relaunching the alarm signal. Complete with foot valves and 3/8 4x6 injections with Viton gaskets, double ceramic ball valves, Teflon diaphragm. PVDF head 2 l/h against 15 bar.

Last update: 23.01.2023



PRODOTTI CHIMICI E TECNICI – CHEMICAL AND TECHNICAL PRODUCTS

FACOT CHEMICALS Srl -Via Crema 44, 26010 Capralba CR, Italy -Tel. +39 0373450642 - info@facot.it - www.facotchemicals.com

