

SKINTOP

Guaina Spray



DESCRIPTION:

Sealing and varnishing filler spray, can be used on uneven surfaces in masonry, asphalt, masonite, wood and many others. It allows the sealing of holes and cracks, preventing the infiltration of water, humidity or the establishment of rust and corrosion. The result will be a smooth, homogeneous surface ready for possible over-painting.

HOW TO USE:

Shake the cylinder vigorously for at least 1 minute, until you feel the inner marbles move freely. Shake even during use. Remove dirt and, if possible, any pre-existing paint. Do not apply to hot surfaces ($> 90^{\circ}\text{C}$). Use outdoors or in a well-ventilated area. Maintain a distance of 20 \div 30 cm when brewing.

APPLICATION:

Apply a first light layer of product and a second layer at least 45 minutes apart. Depending on the depth and size of the slit, the product can be applied at close intervals to obtain a better filling effect. It is recommended to use on inclined and/or flat surfaces. The product may foam and/or bubble. It is possible to overpaint after 24 hours of drying. Once finished, turn the can upside down and spray until the product is completely out to clean the dispenser.

TECHNICAL DATA:

Appearance of cylinder containing liquid under pressure

Black

Characteristic solvent odor

Relative density @ 20 °C 0.96 \div 1.03 g/ml

Flash point < 0°C, extremely flammable

Synthetic resin

Organic solvent

Dry residue in cylinders 18 \div 20%

Application temperature 10 \div 32 °C (humidity < 85%)

Pressure @ 20 °C 4 \div 6 bar

Drying time @ 20 °C Dry to the touch: 45 minutes

Deep dry (overpaintable): 24 hours

STORAGE METHODS:

Before use: Store the product in a dry place at temperatures between +5 °C and +45 °C; keep the containers tightly closed after use. If stored in the original packaging, the product can be stored for a maximum of 18 - 24 months.

After first use: store in a cool, dry place, away from heat sources. Keep out of reach of children.

Last update: 05.01.2024



PRODOTTI CHIMICI E TECNICI - CHEMICAL AND TECHNICAL PRODUCTS

FACOT CHEMICALS Srl -Via Crema 44, 26010 Capralba CR, Italy -Tel. +39 0373450642 - info@facot.it - www.facotchemicals.com