


THERMONET FLUE GAS



DESCRIPTION:

Detergent scale remover for boiler combustion chambers.

Concentrated product, studied to easily remove sooty deposits and incombustible deposits from the flue gas side of heat exchanger surfaces in heating appliances.

INSTRUCTIONS FOR USE:

When sprayed on the boiler surfaces THERMONET FLUE GAS immediately reacts developing effervescence and neutralizing the deposit acidity. Waste is dissolved and softened so that during the following boiler start-up deposits totally come off the surfaces clearing the exchanger from obstructions hence optimizing consumptions. Once the operation is complete, we recommend abundant washing with water, preferably with a pressure jet. It is then recommended to protect and passivate the treated surface (in the case of aluminium or its alloys) using THERMOSAN-BL.

TECHNICAL DATA:

Appearance	liquid
Color	yellow
Odor	characteristic
pH	12,0 ± 0,2
Relative density	1,050 ± 0,010 g/cm ³
Dry residue % @ 105 °C	19,4 ± 1
Water solubility	complete

PACKAGING:

5/10 kg tanks.

INGREDIENTS:

Aqua, Tetrasodium EDTA, Sodium Hydroxide, Acido Alchilbenzensolfonico, Butoxyethanol, Sodio Alchiletere Solfato.

Last update: 17.03.2025



PRODOTTI CHIMICI E TECNICI – CHEMICAL AND TECHNICAL PRODUCTS

FACOT CHEMICALS Srl -Via Crema 44, 26010 Capralba CR, Italy -Tel. +39 0373450642 - info@facot.it - www.facotchemicals.com